




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>B60R 13/08, B62D 25/10</b>	<b>A1</b>	(11) International Publication Number: <b>WO 97/48576</b> (43) International Publication Date: 24 December 1997 (24.12.97)
<p>(21) International Application Number: PCT/KR97/00118</p> <p>(22) International Filing Date: 20 June 1997 (20.06.97)</p> <p>(30) Priority Data: 1996/22837 21 June 1996 (21.06.96) KR</p> <p>(71) Applicant (for all designated States except US): DAEHAN CHEMICAL IND. CO., LTD. [KR/KR]; 9 Block 9 Lot, 616-6, Namchon-dong, Namdong-gu, Inchon 405-100 (KR).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): KWON, Hoe, Hyon [KR/KR]; H-906 Hanyang Apartment, 42, Yoido-dong, Yeongdeungpo-gu, Seoul 150-010 (KR).</p> <p>(74) Agent: LEE, Dae, Sun; 6F Chongkundang Building, 441, Shipchong-2dong, Pupyong-gu, Inchon 403-132 (KR).</p>	<p>(81) Designated States: CN, HU, JP, PL, US, UZ, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published With international search report.</p>	

(54) Title: MULTILAYERED INSULATION SHEET

## (57) Abstract

This invention relates to a multilayered insulation sheet which could effectively reduce the noise level of the inner and outer spaces of the vehicles. According to the invention, there is provided an insulation sheet comprising a foamed plastic layer (12), resin felt layers (11) disposed on either side of said foamed plastic layer (12) and cover sheet (10) which covers the surfaces of said resin felt layers (11), and said insulation sheet (4) is sectioned into the high density region (5) which is made by relatively higher pressured pressing and includes at least the marginal areas of sheet and the low density region (6) which is made by relatively lower pressured pressing and includes the rest areas except said high density region (5).



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## DESCRIPTION

## Title of Invention

Multilayered Insulation Sheet

## Technical Field

This invention relates to a multilayered insulation sheet, and in particular to a multilayered insulation sheet which could effectively reduce the noise level of inner and our space of the vehicles.

## Background Art

Insulation sheets are attached on proper parts of automobiles. These insulation sheets are used to shut off or absorb the noises and vibrations and harshness called N. V. H. for the purpose of quiet and comfortable driving condition.

The known insulation sheets are disposed mainly on the floor panel, door panels, partition between engine room and passenger compartment or partition between passenger compartment and trunk room. These insulation sheets are used to prevent the noise and vibration generating from an engine or powertrain from transmitting or passing into the passenger compartment. But, the design for noise insulation oriented to a quiet passenger compartment could not satisfy the consumer's high

requirement for enhanced standard of quiet cars.

Moreover, the noises going out from the engine room towards the open space may increase directly the noise level of road, and these noises may return to the passenger compartment, which results in increasing the noise of passenger compartment.

Meanwhile, the known insulation sheets are generally composed of one sheets or multilayer sheets which are uniformly pressed to be shaped to predetermined forms. But, those uniformly pressed insulation sheets could not achieve the desired absorption of noises, shape sustenance and workability in attaching process against the panels of vehicles.

#### Disclosure of Invention

One object of invention is to solve the above mentioned problems in relation with the insulation sheets of automobiles and to provide insulation sheets which could effectively reduce the noises going out from the engine room towards the outside of automobiles.

Another object of invention is to provide the insulation sheet which has enhanced property of insulation and shape-sustenance and workability in attaching process.

According to one feature of the invention, there is provided an insulation sheet(4) which is disposed on the inner surface of engine hoods(3) which cover the engine room(2) of vehicle body(1).

According to another feature of the invention, said insulation sheet(4) is comprising a foamed plastic layer(12), resin felt layers(11) disposed on either side of said foamed plastic layer(12) and cover sheet(10) which covers the surfaces of said resin felt layers(11), and said insulation sheet(4) is sectioned into the high density region(5) which is made by relatively higher pressured pressing and includes at least the marginal areas of sheet and the low density region(6) which is made by relatively lower pressured pressing and includes the rest areas except said high density region(5).

According to another feature of the invention, there is provided of an insulation sheet comprising a foamed plastic layer(12), resin felt layers(11) disposed on either side of said foamed plastic layer(12) and cover sheet(10) which covers the surfaces of said resin felt layers(11), and said insulation sheet(4) is sectioned into the high density region(5) which is made by relatively higher pressured pressing and includes at

least the marginal areas of sheet and the low density region(6) which is made by relatively lower pressured pressing and includes the rest areas except said high density region(5).

#### Brief Description of Drawings.

The invention will be described in more detail with reference to the drawings in which :

Fig. 1 is a view showing an exemplary use of the embodiment of the invention.

Fig. 2 is a perspective view of said embodiment.

Fig. 3 is a sectional view according to line A-A of Fig. 2.

#### Best Mode for Carrying out The invention

Referring to the Figures, there is provided an insulation sheet(4) which is disposed and attached to the inner surface of engine hood(3) which covers the engine room(2) of the vehicle body(1). This insulation sheet(4) may be attached to the inner surface of engine hood(3) by means of screw(7). But, other attaching means such as adhesive may be used.

This insulation sheet(4) is made of soft and porous multilayer materials which comprising foamed plastic layer, resin felt layer and

non-woven fabric layer.

In the preferred embodiment shown in Fig. 3, the foamed plastic layer(12) such as polyurethane sponge is disposed in the middle part of multilayer and the resin felt layers(11) made of resin-impregnated felt are disposed on both surfaces of foamed plastic layer(12), and non-woven fabric layers(10) are disposed on the outer surface of resin felt layers(11). If necessary, the non-woven fabric layers(10) may be treated by water-resistant agents.

These insulation sheets(4) may be formed in conformity with the contour of the vehicle body or the shape of vehicle components. As the multilayer sheets made of soft and porous materials are relatively low in shape-sustenance and workability, the marginal areas and intermediate areas of the insulation sheet or fastening areas against vehicle body should be pressed with relatively high pressure to become thinner and rigid high-density regions(5), whereas rest areas of sheets should be pressed with relatively low pressure to become thicker and soft low-density regions(6). Those structure will enhance the insulation property as well as the shape-sustenance and workability. The screw(7) will be fastened at the high density region(5) so that the insulation sheet should be attached against the vehicle body.

According to the invention as described above, as the insulation sheets should be attached on the inner surface of engine hoods(3), the noises going out from the engine room could be effectively reduced, which will firstly reduce the noise level of road on which the car is driving, and will secondly reduce the returning noise from outside the vehicles to the passenger compartment, and finally resulting in more comfortable and quiet driving conditions. In addition, as multilayered insulation sheets comprising soft and porous materials and being sectioned into high density region and low density region will enhance the insulation property as well as the shape-sustenance and workability.



## CLAIMS

1. An insulation sheet(4) which is disposed on the inner surface of engine hood(3) which cover the engine room(2) of vehicle body(1).


2. An insulation sheet according to claim 1 wherein said insulation sheet(4) is comprising a foamed plastic layer(12), resin felt layers(11) disposed on either side of said foamed plastic layer(12) and cover sheet(10) which covers the surfaces of said resin felt layers(11), and said insulation sheet(4) is sectioned into the high density region(5) which is made by relatively higher pressured pressing and includes at least the marginal areas of sheet and the low density region(6) which is made by relatively lower pressured pressing and includes the rest areas parts except said high density region(5).

3. An insulation sheet comprising a foamed plastic layer(12), resin felt layers(11) disposed on either side of said foamed plastic layer(12) and cover sheet(10) which covers the surfaces of said resin felt layers(11), and said insulation sheet(4) is sectioned into the high density region(5) which is made by relatively higher pressured pressing and includes at least the marginal areas of sheet and the low density

region(6) which is made by relatively lower pressured pressing and includes the rest areas except said high density region(5).

$\frac{1}{2}$

FIG. 1



2/2

FIG. 2





FIG. 3



## INTERNATIONAL SEARCH REPORT

International application No.

PCT/KR 97/00118

## A. CLASSIFICATION OF SUBJECT MATTER

IPC<sup>6</sup>: B 60 R 13/08; B 62 D 25/10

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC<sup>6</sup>: B 60 R 13/00,13/08; B 62 D 25/08,25/10,29/00,29/04; B 32 B 5/18,5/26

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPODOC, WPI

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	DE 40 19 121 A1 (SUZUKI) 10 January 1991 (10.01.91), abstract; fig.2.	1 2,3
X Y	DE 39 03 471 A1 (H.P.CHEMIE) 31 August 1989 (31.08.89), column 1, lines 22-51; column 4, lines 20-32.	1 2,3
Y	DE 36 01 204 A1 (DAIMLER) 23 July 1987 (23.07.87), abstract; claim 1.	2,3
A	DE 42 11 409 A1 (MERCEDES) 07 October 1993 (07.10.93), abstract; fig.1,2.	2,3
A	CH 684 398 A5 (MATEC) 15 September 1994 (15.09.94), totality.	1-3
A	US 4 646 864 A (RACCHI) 03 March 1987 (03.03.87), totality.	1-3
----		

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

## \* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

10 September 1997 (10.09.97)

Date of mailing of the international search report

18 September 1997 (18.09.97)

Name and mailing address of the ISA/AT

AUSTRIAN PATENT OFFICE  
Kohlmarkt 8-10  
A-1014 Vienna  
Facsimile No. 1/53424/535

Authorized officer

Pangratz

Telephone No. 1/53424/413

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

International application No.

PCT/KR 97/00118

In Recherchenbericht angeführtes Patentdokument Patent document cited in search report Document de brevet cité dans le rapport de recherche	Datum der Veröffentlichung Publication date Date de publication	Mitglied(er) der Patentfamilie Patent family member(s) Membre(s) de la famille de brevets	Datum der Veröffentlichung Publication date Date de publication
DE A1 4019121	10-01-91	CH A 682384 JP A2 3014777	15-09-93 23-01-91
DE A1 3903471	31-08-89	ES AF 2014577 FR B1 3627127 GB B2 2216062 IE B 60537 KR B1 9201559	16-07-90 10-01-97 04-03-92 27-07-94 18-02-92
DE A1 3601204	23-07-87	DE C0 3682265 EP A2 3229977 EP A3 3229977 EP B1 2229977	05-12-91 28-07-87 25-01-89 30-10-91
DE A1 4211409	07-10-93	FR A1 3689935 FR B1 3689935 GB A0 3689935 GB A1 3689935 GB B2 3689935 IT A0 3689935 IT A 3689935 SE A0 3689935 SE A 3689935	15-10-93 07-10-94 12-05-94 06-10-94 10-05-95 17-05-95 23-05-96 17-05-96 05-10-96
CH A 684398	15-09-94	AT E 116606 DE C0 5920111 EP A1 5111157 EP B1 5111157 ES T 2067319 JP A2 6171436 US A 5567922	15-01-98 16-02-95 28-10-93 04-01-95 16-03-95 21-06-94 22-10-96
US A 4646864	03-03-87	CA A1 1264979	30-01-90